

TXP-H professional pocket transmitter

Technical data



TXP-H professional pocket transmitter

Frequency range	470 – 865MHz (specify at time of order)
Switching bandwidth	Up to 40MHz in 25kHz steps
Number of frequency tables	Up to 10
Number of factory pre-set frequencies	32 in each table
Number of user selectable frequencies	32 in each table (selectable in 25kHz steps)
Manual tune mode	Yes - in 25kHz steps (can be saved to memory)
Modulation mode	Wideband FM
Frequency stability	±0.002%
Audio frequency response	50 – 18kHz
Signal-to-noise ratio	>100dB (±45kHz deviation)
Total harmonic distortion	<0.3% typ.
Output power	100mW or 50mW nominal, selectable
Audio gain control	0-35dB in 8 steps plus 2 steps for line input
LF cut	3 settings; flat, 80Hz, 120Hz
Input connector	Binder™ 5 pin screw-locking
Display	OLED blue, 128x32 pixels
Control	3 position navigation switch
Battery type	1 x 1.5V alkaline LR6 AA size
Battery life	4 to 6 hours depending on battery type Audio recommends using NiMh type batteries
External supply voltage	6 – 18V DC (80mA @ 12V)
Operating temperature range	-20° C to +55° C
Weight	118 grams (without batteries)
Dimensions	63mm (W) x 82mm (H) x 20mm (D)
Accessories	Flexible clear antennae (straight) Input cable (5 pin Binder to XLR female connector) ALM lavalier microphone Neoprene pouch

For further information contact Audio Ltd or your local distributor

www.audioltd.com

As we are always seeking to improve our products, specifications shown are subject to change.