



# XTRAGOOD

1 x 2 passive microphone splitter

## XG12

### XTRAGOOD MICROPHONE SPLITTERS FEATURE:

- All metal “Built Like A Tank” housing
- Ultra-tough finish with laser engraved markings
- Two models: XLR 3-pin or XLR 5-pin versions
- Ground lift with *True Isolation*
- 20 Hz - 20 kHz +/- .05 dB
- THD .005% maximum @ 1 kHz, -10 dB
- Premium quality custom, shielded transformer
- Chassis mounted Neutrik XLR connectors with gold pins
- Common Mode Rejection: 130 dB
- Small footprint at only 4.5” x 2.5” x 1.5”
- Weight: 10.1 ounces



The XG12 passive microphone splitter allows you to “split” and send a balanced microphone signal to two destinations via XLR-3 connectors.

The secondary output has a *True Isolation* Ground Lift to eliminate hum & buzz from ground loops.

Xtragood XG12 1 x 2 is not just an ordinary, “run of the mill” mic splitter. Each unit uses premium components and is built to withstand the extreme punishment of stage and fieldwork. They have a compact housing with all connections conveniently located on one side. The ground lift switch utilizes our custom “finger-friendly” recessed switch guard.

Our passive microphone splitters provide a direct input/output loop with a secondary isolated output via standard XLR-3 connectors. The secondary output has a *True Isolation* ground lift to eliminate hum & buzz from even the worse ground loop situations. Xtragood splitters can be used with many microphone types including condenser, ribbon and dynamic microphones. Phantom power will only be passed through the primary input loop to mic out and not via the secondary isolated output - Great for protecting your vintage ribbon mics.